




2SC3358

NPN SILICON EPITAXIAL TRANSISTOR

HIGH FREQUENCY LOW NOISE AMPLIFIER

FEATURES

- *Low Noise and High Gain
- *High Power Gain



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment				Packing
Lead Free	Halogen Free		1	2	3	4	
2SC3358L-T50-R	2SC3358G-T50-R	TO-50	C	E	B	E	Tape Reel

Note: Pin Assignment: C: Collector E: Emitter B: Base

<p>2SC3358G-T50-R</p> <ul style="list-style-type: none"> (1) Packing Type (2) Package Type (3) Green Package 	<ul style="list-style-type: none"> (1) R: Tape Reel (2) T50: TO-50 (3) G: Halogen Free and Lead Free, L: Lead Free
---	---

■ **ABSOLUTE MAXIMUM RATINGS** ($T_C = 25^\circ\text{C}$, unless otherwise stated)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	V_{CBO}	20	V
Collector-Emitter Voltage	V_{CEO}	12	V
Emitter-Base Voltage	V_{EBO}	3	V
Collector Current	I_C	100	mA
Total Device Dissipation	P_D	250	mW
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-65 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **ELECTRICAL CHARACTERISTICS**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-Off Current	I_{CBO}	$V_{CB}=10\text{V}, I_E=0$			1.0	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=1\text{V}, I_C=0$			1.0	μA
DC Current Gain (Note)	h_{FE}	$V_{CE}=10\text{V}, I_C=20\text{mA}$	50		300	
Transition Frequency	f_T	$V_{CE}=10\text{V}, I_C=20\text{mA}$		7		GHz
Feed-Back Capacitance	C_{re}	$V_{CB}=10\text{V}, I_E=0, f=1.0\text{MHz}$			1.0	pF
Noise figure	NF	$V_{CE}=10\text{V}, I_C=7\text{mA}, f=1.0\text{GHz}$			2.0	dB

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.