



U74HC2G08

CMOS IC


2-INPUT AND GATE

DESCRIPTION

The **U74HC2G08** is a 2-input AND gate which provides the Function $Y=A \times B$.

FEATURES

- * Operation voltage range: 2.0~6.0V
- * Low power dissipation: $I_{CC}=10\mu A$ (Max.)
- * High speed: $t_{PD}=9ns$ ($V_{CC}=4.5V, C_L=50pF$)



ORDERING INFORMATION


Order Number		Package	Packing
Lead Free	Halogen Free		
U74HC2G08L-SM1-R	U74HC2G08G-SM1-R	MSOP-8	Tape Reel
U74HC2G08L-CK08-2030-R	U74HC2G08G-CK08-2030-R	CDFN2030-8	Tape Reel

<p>U74HC2G08G-SM1-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) SM1: MSOP-8, CK08-2030: CDFN2030-8</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	--

MARKING

MSOP-8	CDFN2030-8
<p>8 7 6 5 → Date Code</p> <p>UTC □□□□</p> <p>HC2G08 □</p> <p>→ L: Lead Free</p> <p>→ G: Halogen Free</p> <p>→ Lot Code</p> <p>1 2 3 4</p>	<p>HC</p> <p>2G08</p> <p>• □□□□ → Date Code</p>

■ PIN CONFIGURATION



■ FUNCTION TABLE (each gate)

INPUT(A)	INPUT(B)	OUTPUT(Y)
L	L	L
L	H	L
H	L	L
H	H	H

■ LOGIC DIAGRAM (positive logic)



■ ABSOLUTE MAXIMUM RATINGS (unless otherwise specified)(Note 1)

PARAMETER		SYMBOL	RATINGS	UNIT
Supply Voltage		V_{CC}	-0.5 ~ +7.0	V
Input Voltage		V_{IN}	-0.5 ~ +7.0	V
Output Voltage		V_{OUT}	-0.5 ~ $V_{CC}+0.5$	V
Input Clamp Current		I_{IK}	±20	mA
Output Clamp Current		I_{OK}	±20	mA
Output Current		I_{OUT}	25	mA
V_{CC} or GND Current		I_{CC}	±50	mA
Power dissipation	MSOP-8	P_D	300	mW
	CDFN2030-8			mW
Storage Temperature		T_{STG}	-65 ~ +150	°C

Note 1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

2. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		2.0	5.0	6.0	V
Input Voltage	V_{IN}		0		V_{CC}	V
Output Voltage	V_{OUT}		0		V_{CC}	V
Input Transition Rise or Fall Times	t_R, t_F	$V_{CC}=2.0V$			1000	ns
		$V_{CC}=4.5V$		6	500	ns
		$V_{CC}=6V$			400	ns
Operating Temperature	T_A		-40	+25	+125	°C

■ STATIC CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-Level Input Voltage	V_{IH}	$V_{CC}=2.0V$	1.5	1.2		V
		$V_{CC}=4.5V$	3.15	2.4		V
		$V_{CC}=6.0V$	4.2	3.2		V
Low-Level Input Voltage	V_{IL}	$V_{CC}=2.0V$		0.8	0.5	V
		$V_{CC}=4.5V$		2.1	1.35	V
		$V_{CC}=6.0V$		2.8	1.8	V
High-Level Output Voltage	V_{OH}	$V_{CC}=2.0V, I_{OH}=-20\mu A$	1.9	2.0		V
		$V_{CC}=4.5V, I_{OH}=-20\mu A$	4.4	4.5		V
		$V_{CC}=6.0V, I_{OH}=-20\mu A$	5.9	6.0		V
		$V_{CC}=4.5V, I_{OH}=-4mA$	4.13	4.32		V
		$V_{CC}=6.0V, I_{OH}=-5.2mA$	5.63	5.81		V
Low-Level Output Voltage	V_{OL}	$V_{CC}=2.0V, I_{OL}=20\mu A$		0	0.1	V
		$V_{CC}=4.5V, I_{OL}=20\mu A$		0	0.1	V
		$V_{CC}=6.0V, I_{OL}=20\mu A$		0	0.1	V
		$V_{CC}=4.5V, I_{OL}=4mA$		0.15	0.33	V
		$V_{CC}=6.0V, I_{OL}=5.2mA$		0.16	0.33	V
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=6.0V, V_{IN}=V_{CC}$ or GND			±1	μA
Quiescent Supply Current	I_Q	$V_{CC}=6.0V, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0A$			10	μA
Input Capacitance	C_{IN}	$V_{CC}=5.0V, V_{IN}=V_{CC}$ or GND		1.5		pF

■ DYNAMIC CHARACTERISTICS (Input: $t_R, t_F \leq 6\text{ns}; \text{PRR} \leq 1\text{MHz};$)


See Fig. 1 and Fig. 2 for test circuit and waveforms.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation Delay From Input (A and B) to output(Y)	t_{PHL} / t_{PLH}	$V_{CC}=2.0\text{V}, C_L=50\text{pF}$		26	95	ns
		$V_{CC}=4.5\text{V}, C_L=50\text{pF}$		9	19	ns
		$V_{CC}=6.0\text{V}, C_L=50\text{pF}$		8	16	ns
Output transition Time	t_{THL} / t_{TLH}	$V_{CC}=2.0\text{V}, C_L=50\text{pF}$		20	95	ns
		$V_{CC}=4.5\text{V}, C_L=50\text{pF}$		7	19	ns
		$V_{CC}=6.0\text{V}, C_L=50\text{pF}$		6	16	ns

■ OPERATING CHARACTERISTICS


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C_{PD}	No load, $V_{CC}=5\text{V}, f=1\text{MHz}$		10		pF

■ TEST CIRCUIT AND WAVEFORMS



Note: CL includes probe and jig capacitance.

Load circuitry for switching times.



Propagation delay from input(A and B) to output(Y) and Output transition time.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.