



U74HCT21

CMOS IC


DUAL 4-INPUT AND GATES

DESCRIPTION

The **U74HCT21** contains two independent 4-input AND gates. They perform the Boolean function $Y=A \bullet B \bullet C \bullet D$ or $Y=\overline{A} + \overline{B} + \overline{C} + \overline{D}$ in positive logic.

FEATURES

- * Operation Voltage Range: 4.5V~5.5V
- * Low Quiescent Current: $I_{CC}=2\mu A(\text{Max})$
- * High Speed: $t_{PD}=15\text{ns @ }4.5\text{V (Typ)}$
- * Low Input Current: 100nA Max
- * Inputs are TTL Voltage Compatiabel




ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74HCT21L-P14-R	U74HCT21G-P14-R	TSSOP-14	Tape Reel

<p>U74HCT21G-P14-R</p> <p>(1) Packing Type (2) Package Type (3) Green Package</p>	<p>(1) R: Tape Reel (2) P14: TSSOP-14 (3) G: Halogen Free and Lead Free, L: Lead Free</p>
-------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------

MARKING




■ PIN CONFIGURATION



■ FUNCTION TABLE

INPUT(A)	INPUT(B)	INPUT(C)	INPUT(D)	OUTPUT(Y)
H	H	H	H	H
L	X	X	X	L
X	L	X	X	L
X	X	L	X	L
X	X	X	L	L

■ LOGIC DIAGRAM (positive logic)



■ ABSOLUTE MAXIMUM RATING (Unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5 ~ 7	V
Input Clamp Current	I_{IK}	±20	mA
Output Clamp Current	I_{OK}	±20	mA
Output Current	I_{OUT}	±25	mA
V_{CC} or GND Current	I_{CC}	±50	mA
Storage Temperature	T_{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS (Unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		4.5		5.5	V
Input Voltage	V_{IN}		0		V_{CC}	V
Output Voltage	V_{OUT}		0		V_{CC}	V
Input Rise and Fall Times	t_R, t_F	$V_{CC}=4.5V$			500	ns
Operating Temperature	T_A		-40		+125	°C

■ STATIC CHARACTERISTICS (Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-Level Input Voltage	V_{IH}	$V_{CC}= 4.5V$ to 5.5V	2.0			V
Low-Level Input Voltage	V_{IL}	$V_{CC}= 4.5V$ to 5.5V			0.8	V
High-Level Output Voltage	V_{OH}	$V_{CC}= 4.5V, I_O = -20\mu A$	4.4	4.999		V
		$V_{CC}= 4.5V, I_O = -4mA$	3.98	4.3		
Low-Level Output Voltage	V_{OL}	$V_{CC}= 4.5V, I_O = 20\mu A$		0.001	0.1	V
		$V_{CC}= 4.5V, I_O = 4mA$		0.17	0.26	
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}= 5.5V, V_{IN} = V_{CC}$ or GND		±0.1	±100	nA
Quiescent Supply Current	I_{CC}	$V_{CC}= 5.5V, V_{IN} = V_{CC}$ or GND, $I_O = 0$			2	μA
Additional Quiescent Supply Current	ΔI_{CC}	One input at $V_{CC} - 2.1V$, other inputs at 0 or V_{CC}		100	360	uA
Input Capacitance	C_{IN}	$V_{CC}=4.5V\sim 5.5V$		3	10	pF


■ DYNAMIC CHARACTERISTICS (Input: $t_R=t_F=6ns$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from Input(A or B) to Output(Y)	t_{PLH}, t_{PHL}	$V_{CC}=4.5V, C_L=50pF$		15	27	ns
Output Transition Time	t_T	$V_{CC}=4.5V, C_L=50pF$		7	15	ns


■ OPERATING CHARACTERISTICS (Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	RATINGS	UNIT
Power Dissipation Capacitance	C_{PD}	No Load	42	pF

■ TEST CIRCUIT AND WAVEFORMS



Note : C_L includes probe and jig capacitance.



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.