



## UCD4060B

CMOS IC

### CMOS 14-STAGE RIPPLE-CARRY BINARY COUNTER/DIVIDER AND OSCILLATOR

#### ■ DESCRIPTION

**UCD4060B** consists of an oscillator section and 14 ripple-carry binary counter stages. The oscillator configuration allows design of either  $R_C$  or crystal oscillator circuits. A RESET input is provided which resets the counter to the all-O's state and disables the oscillator. A high level on the RESET line accomplishes the reset function. All counter stages are master-slave flip-flops. The state of the counter is advanced one step in binary order on the negative transition of  $\Phi I$  and  $\Phi O$ . All inputs and outputs are fully buffered. Schmitt trigger action on the input-pulse line permits unlimited input-pulse rise and fall times.

#### ■ FEATURES


- \* 12MHz clock rate at 15V
- \* Common reset
- \* Fully static operation
- \* Buffered inputs and outputs
- \* Schmitt trigger input-pulse line

#### ■ OSCILLATOR FEATURES

- \* All active components on chip
- \* RC or crystal oscillator configuration
- \* RC oscillator frequency of 690 kHz min. at 15V


#### ■ APPLICATIONS

- \* Control counters
- \* Timers
- \* Frequency dividers
- \* Time-delay circuits




■ ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
UCD4060BL-D16-T	UCD4060BG-D16-T	DIP-16	Tube
UCD4060BL-S16-R	UCD4060BG-S16-R	SOP-16	Tape Reel
UCD4060BL-P16-R	UCD4060BG-P16-R	TSSOP-16	Tape Reel




■ MARKING



## ■ PIN CONFIGURATION



## ■ LOGIC DIAGRAM



■ ABSOLUTE MAXIMUM RATING (Unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	$V_{DD}$	-0.5 ~ 20	V
Input Voltage	$V_{IN}$	-0.5 ~ $V_{CC}+0.5$	V
Output Voltage	$V_{OUT}$	-0.5 ~ $V_{CC}+0.5$	V
Input Clamp Current ( $V_{IN}<0$ , or $V_{IN}>V_{DD}$ )	$I_{IK}$	$\pm 10$	mA
Power Dissipation ( $T_A=-40^{\circ}\text{C}\sim+125^{\circ}\text{C}$ )	$P_D$	500	mW
Storage Temperature	$T_{STG}$	-65 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	CONDITIONS	MIN	TPY	MAX	UNIT
Supply Voltage	$V_{DD}$		3		18	V
Input-Pulse Width	$t_w$	$V_{DD}=5\text{V}$	100			ns
		$V_{DD}=10\text{V}$	40			ns
		$V_{DD}=15\text{V}$	30			ns
Input-Pulse Frequency	$f_{\phi I}$	$V_{DD}=5\text{V}$			3.5	MHz
		$V_{DD}=10\text{V}$			8	MHz
		$V_{DD}=15\text{V}$			12	MHz
Input-Pulse Rise and Fall Time	$t_r / t_f$	$V_{DD}=5\text{V}$	Unlimited			$\mu\text{s}$
		$V_{DD}=10\text{V}$				$\mu\text{s}$
		$V_{DD}=15\text{V}$				$\mu\text{s}$
Reset Pulse Width	$t_w$	$V_{DD}=5\text{V}$	120			ns
		$V_{DD}=10\text{V}$	60			ns
		$V_{DD}=15\text{V}$	40			ns
Operating Temperature	$T_A$		-40		+125	$^{\circ}\text{C}$

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	DIP-16	69	$^{\circ}\text{C}/\text{W}$
	SOP-16	90	$^{\circ}\text{C}/\text{W}$
	TSSOP-16	110	$^{\circ}\text{C}/\text{W}$

■ ELECTRICAL CHARACTERISTICS (Unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS	MIN	TPY	MAX	UNIT
Quiescent Supply Current	$I_{CC}$	$V_{IN}=0, 5V, V_{DD}=5V$		0.04	5	$\mu A$
		$V_{IN}=0, 10V, V_{DD}=10V$		0.04	10	
		$V_{IN}=0, 15V, V_{DD}=15V$		0.04	20	
		$V_{IN}=0, 20V, V_{DD}=20V$		0.08	100	
Output Low (Sink) Current	$I_{OL}$	$V_{OUT}=0.4V, V_{IN}=0, 5V, V_{DD}=5V$	0.51	1		mA
		$V_{OUT}=0.5V, V_{IN}=0, 10V, V_{DD}=10V$	1.3	2.6		
		$V_{OUT}=1.5V, V_{IN}=0, 15V, V_{DD}=15V$	3.4	6.8		
Output High (Source) Current	$I_{OH}$	$V_{OUT}=4.6V, V_{IN}=0, 5V, V_{DD}=5V$	-0.51	-1		mA
		$V_{OUT}=2.5V, V_{IN}=0, 5V, V_{DD}=5V$	-1.6	-3.2		
		$V_{OUT}=9.5V, V_{IN}=0, 10V, V_{DD}=10V$	-1.3	-2.6		
		$V_{OUT}=13.5V, V_{IN}=0, 15V, V_{DD}=15V$	-3.4	-6.8		
Output Voltage: Low-Level	$V_{OL}$	$V_{IN}=0, 5V, V_{DD}=5V$		0	0.05	V
		$V_{IN}=0, 10V, V_{DD}=10V$		0	0.05	
		$V_{IN}=0, 15V, V_{DD}=15V$		0	0.05	
Output Voltage: High-Level	$V_{OH}$	$V_{IN}=0, 5V, V_{DD}=5V$	4.95	5		V
		$V_{IN}=0, 10V, V_{DD}=10V$	9.95	10		
		$V_{IN}=0, 15V, V_{DD}=15V$	14.95	15		
Input Low Voltage	$V_{IL}$	$V_{OUT}=0.5, 4.5V, V_{DD}=5V$			1.5	V
		$V_{OUT}=1, 9V, V_{DD}=10V$			3	
		$V_{OUT}=1.5, 13.5V, V_{DD}=15V$			4	
Input High Voltage	$V_{IH}$	$V_{OUT}=0.5, 4.5V, V_{DD}=5V$	3.5			V
		$V_{OUT}=1, 9V, V_{DD}=10V$	7			
		$V_{OUT}=1.5, 13.5V, V_{DD}=15V$	11			
Input Leakage Current	$I_{I(LEAK)}$	$V_{IN}=0, 18V, V_{DD}=18V$		$\pm 10^{-5}$	$\pm 0.1$	$\mu A$

■ SWITCHING CHARACTERISTICS

(UInput  $t_r / t_f=20ns, C_L=50pF, R_L=200k\Omega$ , Unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS	MIN	TPY	MAX	UNIT
<b>CLOCKED OPERATION</b>						
Propagation Delay Time, $\Phi I$ to Q4	$t_{PLH} / t_{PHL}$	$V_{DD}=5V$		370	740	ns
		$V_{DD}=10V$		150	300	
		$V_{DD}=15V$		100	200	
Propagation Delay Time, $Q_n$ to $Q_{n+1}$	$t_{PLH} / t_{PHL}$	$V_{DD}=5V$		100	200	ns
		$V_{DD}=10V$		50	100	
		$V_{DD}=15V$		40	80	
Transition Time	$t_{THL} / t_{TLH}$	$V_{DD}=5V$		100	200	ns
		$V_{DD}=10V$		50	100	
		$V_{DD}=15V$		40	80	
Maximum Input-Pulse Frequency	$f_{\Phi I}$	$V_{DD}=5V$	3.5	7		MHz
		$V_{DD}=10V$	8	16		
		$V_{DD}=15V$	12	24		
Minimum Input-Pulse Width	$t_w$	$V_{DD}=5V$		50	100	ns
		$V_{DD}=10V$		20	40	
		$V_{DD}=15V$		15	30	
Input-Pulse Rise and Fall Time	$t_r \Phi / t_f \Phi$	$V_{DD}=5V$	Unlimited			
		$V_{DD}=10V$				
		$V_{DD}=15V$				
Average Input Capacitance	$C_I$	Any Input		5	7.5	pF

■ SWITCHING CHARACTERISTICS (Cont.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TPY	MAX	UNIT	
<b>RESET OPERATION</b>							
Propagation Delay Time	$t_{PLH} / t_{PHL}$	$V_{DD}=5V$		180	360	ns	
		$V_{DD}=10V$		80	160	ns	
		$V_{DD}=15V$		50	100	ns	
Minimum Reset Pulse Width	$t_{WR}$	$V_{DD}=5V$		60	120	ns	
		$V_{DD}=10V$		30	60	ns	
		$V_{DD}=15V$		20	40	ns	
<b>RC OPERATION</b>							
Variation of Frequency		$C_X=200pF,$ $R_S=560k\Omega,$ $R_X=50k\Omega$	$V_{DD}=5V$		23±10%		kHz
			$V_{DD}=10V$		24±10%		kHz
			$V_{DD}=15V$		25±10%		kHz
Variation of Frequency with voltage change		$C_X=200pF,$ $R_S=560k\Omega,$ $R_X=50k\Omega$	$V_{DD}=5V\sim 10V$		1.5		kHz
			$V_{DD}=10V\sim 15V$		0.5		kHz
$R_X$ max			$C_X=10mF, V_{DD}=5V$			20	MΩ
			$C_X=50\mu F, V_{DD}=10V$			20	MΩ
			$C_X=10\mu F, V_{DD}=15V$			10	MΩ
$C_X$ max			$R_X=500k\Omega, V_{DD}=5V$			1000	μF
			$R_X=300k\Omega, V_{DD}=10V$			50	
			$R_X=300k\Omega, V_{DD}=15V$			50	
Maximum Oscillator Frequency		$C_X=15pF,$ $R_S=30k\Omega,$ $R_X=5k\Omega$	$V_{DD}=10V$	530	650	810	kHz
			$V_{DD}=15V$	690	800	940	kHz
Drive Current at Pin 9	$I_{OL}$		$V_O=0.4V, V_{DD}=5V$	0.16	0.35		mA
			$V_O=0.5V, V_{DD}=10V$	0.42	0.8		mA
			$V_O=1.5V, V_{DD}=15V$	1	2		mA
	$I_{OH}$		$V_O=4.6V, V_{DD}=5V$	-0.16	-0.35		mA
			$V_O=9.5V, V_{DD}=10V$	-0.42	-0.8		mA
			$V_O=13.5V, V_{DD}=15V$	-1	-2		mA

■ TEST CIRCUIT AND WAVEFORMS




Fig. 1 Test Circuit

Inputs		$V_M$	$V_{LOAD}$	$C_L$	$R_L$
$V_{IN}$	$t_r, t_f$				
$V_{CC}$	20 ns	$V_{CC}/2$	$V_{CC}$	50 pF	200 K $\Omega$




Fig. 2 Voltage Waveforms Input Rise And Fall Times




Fig. 3 Voltage Waveforms Propagation Delay And Output Transition Times

- Notes: 1.  $C_L$  includes probe and jig capacitance.
- 2. All input pulses are supplied by generators having the following characteristics: PRR  $\leq$  1MHz,  $Z_0 = 50\Omega$ .

■ TEST CIRCUIT AND WAVEFORMS (Cont.)




Fig. 4 Dynamic Power Dissipation Test Circuit




Fig. 5 Typical RC Circuit

■ TEST CIRCUIT AND WAVEFORMS (Cont.)




Fig. 6 Quiescent device current test circuit





Fig. 7 Input voltage test circuit

## ■ TEST CIRCUIT AND WAVEFORMS (Cont.)

**Fig. 8 Input current test circuit**

Note: Measure inputs sequentially, to both  $V_{DD}$  and  $V_{SS}$ ; Connect all unused inputs to either  $V_{DD}$  or  $V_{SS}$ .

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.