



UMUR2520

Preliminary

DIODE


SUPER FAST RECOVERY RECTIFIER

DESCRIPTION

The UTC **UMUR2520** a super fast recovery rectifier, it uses UTC's advanced technology to provide customers with high switching speed, high efficiency and low Leakage current, etc.

FEATURES

- * Low forward voltage drop
- * High switching speed
- * High efficiency
- * Low leakage current



SYMBOL



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UMUR2520L-TA2-T	UMUR2520G-TA2-T	TO-220-2	K	A	NC	Tube

Note: Pin Assignment: A: Anode, K: Cathode

<p>UMUR2520L-TA2-T</p> <ul style="list-style-type: none"> (1)Packing Type (2)Package Type (3)Halogen Free 	<ul style="list-style-type: none"> (1) T: Tube (2) TA2: TO-220-2 (3) L: Lead Free, G: Halogen Free
--	---

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
DC Blocking Voltage	V_R	200	V
Recurrent Peak Reverse Voltage	V_{RRM}	200	V
RMS Voltage	V_{RMS}	40	V
Operating Temperature	T_J	-65~+175	°C
Storage Temperature	T_{STG}	-65~+175	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$, unless otherwise specified.)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Average Forward Current	$I_{F(AV)}$	$T_L=145^\circ\text{C}$		25		A
Peak Forward Surge Current	I_{FSM}	8.3ms, half sine		500		A
Instantaneous Forward Voltage	V_F	$I_{FM}=25\text{A}$, $T_A=25^\circ\text{C}$			0.950	V
DC Reverse Current At Rated DC Blocking Voltage	I_R	$T_A=25^\circ\text{C}$			10	μA
Reverse Recovery Time	T_{rr}	$F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{rr}=0.25\text{A}$			50	ns
Junction Capacitance	C_J	Measured at 1.0MHz, $V_R=4.0\text{V}$		100		pF

Note: Pulse Test: Pulse Width 300 μsec , Duty Cycle 1%

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.