



## 4N90-N

Power MOSFET

### 4 Amps, 900 Volts N-CHANNEL POWER MOSFET

#### DESCRIPTION


The UTC **4N90-N** is a N-channel enhancement MOSFET adopting UTC's advanced technology to provide customers with DMOS, planar stripe technology. This technology is designed to meet the requirements of the minimum on-state resistance and perfect switching performance. It also can withstand high energy pulse in the avalanche and communication mode.

The UTC **4N90-N** is particularly applied in high efficiency switch mode power supplies.

#### FEATURES

- \*  $R_{DS(ON)} < 4.2\Omega @ V_{GS}=10V, I_D=2A$
- \* High switching speed
- \* 100% avalanche tested
- \* Improved dv/dt capability

#### SYMBOL





#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
4N90L-TM3-T	4N90G-TM3-T	TO-251	G	D	S	Tube
4N90L-TN3-R	4N90G-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>4N90L-TA3-T</p> <p>(1) Packing Type (2) Package Type (3) Green Package</p>	<p>(1) T: Tube, R: Tape Reel (2) TM3: TO-251, TN3: TO-252 (3) L: Lead Free, G: Halogen Free and Lead Free</p>
---	---

#### MARKING



■ ABSOLUTE MAXIMUM RATINGS ( $T_C=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain to Source Voltage	$V_{DSS}$	900	V
Gate to Source Voltage	$V_{GSS}$	$\pm 30$	V
Avalanche Current (Note 2)	$I_{AR}$	4	A
Continuous Drain Current	Continuous	$I_D$	4
	Pulsed (Note 2)	$I_{DM}$	16
Avalanche Energy	Single Pulsed (Note 3)	$E_{AS}$	240
	Repetitive (Note 2)	$E_{AR}$	14
Peak Diode Recovery dv/dt (Note 4)	dv/dt	4.5	V/ns
Power Dissipation ( $T_C=25^\circ\text{C}$ )	$P_D$	54	W
Derate above $25^\circ\text{C}$		0.43	W/ $^\circ\text{C}$
Operating Junction Temperature	$T_J$	+150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature

3.  $L=30\text{mH}$ ,  $I_{AS}=4\text{A}$ ,  $V_{DD}=50\text{V}$ ,  $R_G=25\Omega$ , Starting  $T_J=25^\circ\text{C}$

4.  $I_{SD}\leq 4\text{A}$ ,  $di/dt\leq 200\text{A}/\mu\text{s}$ ,  $V_{DD}\leq BV_{DSS}$ , Starting  $T_J=25^\circ\text{C}$

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	$\theta_{JA}$	110	$^\circ\text{C}/\text{W}$
Junction to Case	$\theta_{JC}$	2.3	$^\circ\text{C}/\text{W}$


■ ELECTRICAL CHARACTERISTICS (T<sub>C</sub>=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	900			V
Breakdown Voltage Temperature Coefficient	ΔBV <sub>DSS</sub> /ΔT <sub>J</sub>	I <sub>D</sub> =250μA, Referenced to 25°C		1.05		V/°C
Drain-Source Leakage Current	I <sub>DSS</sub>	V <sub>DS</sub> =900V, V <sub>GS</sub> =0V			10	μA
		V <sub>DS</sub> =720V, T <sub>C</sub> =125°C			100	μA
Gate- Source Leakage Current	Forward	I <sub>GSS</sub> V <sub>GS</sub> =+30V, V <sub>DS</sub> =0V			+100	nA
	Reverse	I <sub>GSS</sub> V <sub>GS</sub> =-30V, V <sub>DS</sub> =0V			-100	nA
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	V <sub>GS(TH)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	3.0		5.0	V
Drain-Source On-State Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =2A		3.5	4.2	Ω
<b>DYNAMIC PARAMETERS</b>						
Input Capacitance	C <sub>ISS</sub>	V <sub>DS</sub> =25V, V <sub>GS</sub> =0V, f=1.0MHz		900		pF
Output Capacitance	C <sub>OSS</sub>			67		pF
Reverse Transfer Capacitance	C <sub>RSS</sub>			50		pF
<b>SWITCHING PARAMETERS</b>						
Total Gate Charge	Q <sub>G</sub>	V <sub>DS</sub> =50V, V <sub>GS</sub> =10V, I <sub>D</sub> =1.3A (Note 1,2)		38		nC
Gate-Source Charge	Q <sub>GS</sub>			7.5		nC
Gate-Drain Charge	Q <sub>GD</sub>			8.8		nC
Turn-ON Delay Time	t <sub>D(ON)</sub>	V <sub>DD</sub> =30V, I <sub>D</sub> =0.5A, R <sub>G</sub> =25Ω (Note 1,2)		65		ns
Turn-ON Rise Time	t <sub>R</sub>			56		ns
Turn-OFF Delay Time	t <sub>D(OFF)</sub>			130		ns
Turn-OFF Fall Time	t <sub>F</sub>			50		ns
<b>SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS</b>						
Maximum Body-Diode Continuous Current	I <sub>S</sub>				4	A
Maximum Body-Diode Pulsed Current	I <sub>SM</sub>				16	A
Drain-Source Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =4A, V <sub>GS</sub> =0V			1.4	V


Notes: 1. Pulse Test : Pulse width≤300μs, Duty cycle≤2%

2. Essentially independent of operating temperature

## TEST CIRCUITS AND WAVEFORMS




**Peak Diode Recovery dv/dt Test Circuit**




**Peak Diode Recovery dv/dt Waveforms**


## TEST CIRCUITS AND WAVEFORMS (Cont.)




**Switching Test Circuit**




**Switching Waveforms**




**Gate Charge Test Circuit**



**Gate Charge Waveform**







**Unclamped Inductive Switching Test Circuit**



**Unclamped Inductive Switching Waveforms**

## TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.