

4N80-C

Power MOSFET

4.0A, 800V N-CHANNEL POWER MOSFET

■ DESCRIPTION



The UTC **4N80-C** is a N-channel mode power MOSFET using UTC's advanced technology to provide customers planar stripe and DMOS technology. This technology is specialized in allowing a minimum on-state resistance, and superior switching performance. It also can withstand high energy pulse in the avalanche and commutation mode.

The UTC **4N80-C** is universally applied in high efficiency switch mode power supply.

■ FEATURES

- * $R_{DS(on)} \leq 2.6 \Omega$ @ $V_{GS}=10V$, $I_D=2.0A$
- * High switching speed
- * Improved dv/dt capability
- * 100% avalanche tested


■ SYMBOL




■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
4N80L-TA3-T	4N80G-TA3-T	TO-220	G	D	S	Tube
4N80L-TF1-T	4N80G-TF1-T	TO-220F1	G	D	S	Tube
4N80L-TM3-T	4N80G-TM3-T	TO-251	G	D	S	Tube
4N80L-TN3-R	4N80G-TN3-R	TO-252	G	D	S	Tape Reel
4N80L-TND-R	4N80G-TND-R	TO-252D	G	D	S	Tape Reel
4N80L-T2Q-T	4N80G-T2Q-T	TO-262	G	D	S	Tube
4N80L-TQ2-T	4N80G-TQ2-T	TO-263	G	D	S	Tube
4N80L-TQ2-R	4N80G-TQ2-R	TO-263	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

 (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF1: TO-220F1, TM3: TO-251, TN3: TO-252, TND: TO-252D, T2Q: TO-262, TQ2: TO-263 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_c=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	800	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	4	A
	Pulsed (Note 2)	I_{DM}	8	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	369	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	2.5	V/ns
Power Dissipation	TO-220/TO-262	P_D	106	W
	TO-263		28	W
	TO-220F1		47	W
	TO-251/ TO-252			
	TO-252D			
Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature

3. L=57mH, $I_{AS}=3.6\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$

4. $I_{SD} \leq 4\text{A}$, $dI/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J=25^\circ\text{C}$

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220/TO-220F1	θ_{JA}	62.5	$^\circ\text{C/W}$
	TO-262/TO-263		110	$^\circ\text{C/W}$
Junction to Case	TO-251/ TO-252	θ_{JC}	1.18	$^\circ\text{C/W}$
	TO-252D		4.46	$^\circ\text{C/W}$
	TO-220/TO-262		2.65 (Note)	$^\circ\text{C/W}$
	TO-263			
	TO-220F1			

Note: Device mounted on FR-4 substrate P_C board, 2oz copper, with 1inch square copper plate.


■ ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	800			V
Breakdown Voltage Temperature Coefficient	$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	$I_{\text{D}}=250\mu\text{A}$, Referenced to 25°C		900		mV°C
Drain-Source Leakage Current	I_{DSS}	$V_{\text{DS}}=800\text{V}, V_{\text{GS}}=0\text{V}$		10		μA
		$V_{\text{DS}}=640\text{V}, T_c=125^\circ\text{C}$		100		μA
Gate-Source Leakage Current	Forward	$V_{\text{DS}}=0\text{V}, V_{\text{GS}}=30\text{V}$		100		nA
	Reverse	$V_{\text{DS}}=0\text{V}, V_{\text{GS}}=-30\text{V}$		-100		nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{\text{GS(TH)}}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	3.0		5.0	V
Drain-Source On-State Resistance	$R_{\text{DS(ON)}}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=2.0\text{A}$			2.6	Ω
DYNAMIC PARAMETERS						
Input Capacitance	C_{ISS}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1.0\text{MHz}$		870		pF
Output Capacitance	C_{OSS}			105		pF
Reverse Transfer Capacitance	C_{RSS}			12		pF
SWITCHING PARAMETERS						
Total Gate Charge (Note 1)	Q_G	$V_{\text{DS}}=640\text{V}, V_{\text{GS}}=10\text{V}, I_{\text{D}}=4.0\text{A}$ (Note 1,2)		32		nC
Gate-Source Charge	Q_{GS}			12		nC
Gate-Drain Charge	Q_{GD}			9		nC
Turn-ON Delay Time (Note 1)	$t_{\text{D(ON)}}$	$V_{\text{DD}}=400\text{V}, I_{\text{D}}=4.0\text{A}, R_{\text{G}}=25\Omega$ (Note 1,2)		16		ns
Turn-ON Rise Time	t_{R}			20		ns
Turn-OFF Delay Time	$t_{\text{D(OFF)}}$			70		ns
Turn-OFF Fall Time	t_{F}			34		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Body-Diode Continuous Current	I_S				4	A
Maximum Body-Diode Pulsed Current	I_{SM}				8	A
Drain-Source Diode Forward Voltage (Note 1)	V_{SD}	$I_S=4.0\text{A}, V_{\text{GS}}=0\text{V}$			1.4	V
Body Diode Reverse Recovery Time (Note 1)	t_{rr}	$I_S=4.0\text{A}, V_{\text{GS}}=0\text{V}, dI_F/dt=100\text{A}/\mu\text{s}$ (Note 1)		520		ns
Body Diode Reverse Recovery Charge	Q_{rr}			4.3		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.