



11NM60-U2

Power MOSFET

11A, 600V N-CHANNEL SUPER-JUNCTION MOSFET


DESCRIPTION

The **UTC 11NM60-U2** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at AC-DC converters for power applications.

FEATURES

- * $R_{DS(ON)} \leq 0.5 \Omega @ V_{GS}=10V, I_D=5.5A$
- * By using Super Junction Structure
- * Fast Switching
- * With 100% Avalanche Tested

SYMBOL




ORDERING INFORMATION


Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
11NM60L-TA3-T	11NM60G-TA3-T	TO-220	G	D	S	Tube
11NM60L-TF3-T	11NM60G-TF3-T	TO-220F	G	D	S	Tube
11NM60L-TF1-T	11NM60G-TF1-T	TO-220F1	G	D	S	Tube
11NM60L-TW1-T	11NM60G-TW1-T	TO-220WF	G	D	S	Tube
11NM60L-TM3-T	11NM60G-TM3-T	TO-251	G	D	S	Tube
11NM60L-TN3-R	11NM60G-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>11NM60G-TA3-T</p> <p>(1)Packing Type</p> <p>(2)Package Type</p> <p>(3)Green Package</p>	<p>(1) T: Tube, R: Tape Reel</p> <p>(2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1, TW1: TO-220WF, TM3: TO-251, TN3: TO-252</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	--



■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_c = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	600	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	11	A
	Pulsed (Note 2)	I_{DM}	33	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	425	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	18	V/ns
Power Dissipation	TO-220	P_D	80	W
	TO-220F/TO-220F1		30	W
	TO-220WF			
	TO-251/TO-252		60	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=132\text{mH}$, $I_{AS}=2.54\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$

4. $I_{SD} \leq 11\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J=25^\circ\text{C}$

■ THERMAL DATA

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F	θ_{JA}	62.5	$^\circ\text{C}/\text{W}$
	TO-220F1/TO-220WF			
	TO-251/TO-252			
Junction to Case	TO-220	θ_{JC}	1.56	$^\circ\text{C}/\text{W}$
	TO-220F/TO-220F1		4.16	$^\circ\text{C}/\text{W}$
	TO-220WF			
	TO-251/TO-252		2.08	$^\circ\text{C}/\text{W}$


■ ELECTRICAL CHARACTERISTICS (T_J=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	600			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =600V, V _{GS} =0V			10	μA
Gate-Source Leakage Current	Forward	I _{GSS} V _{DS} =0V, V _{GS} =30V			100	nA
	Reverse		V _{DS} =0V, V _{GS} =-30V			-100
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.5		4.5	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =5.5A			0.5	Ω
DYNAMIC PARAMETERS						
Input Capacitance	C _{ISS}	V _{GS} =0V, V _{DS} =50V, f=1.0MHz		630		pF
Output Capacitance	C _{OSS}			80		pF
Reverse Transfer Capacitance	C _{RSS}			3		pF
SWITCHING PARAMETERS						
Total Gate Charge (Note 1)	Q _G	V _{DS} =100V, V _{GS} =10V, I _D =11A (Note 1, 2)		26		nC
Gate to Source Charge	Q _{GS}			8		nC
Gate to Drain Charge	Q _{GD}			10		nC
Turn-ON Delay Time (Note 1)	t _{D(ON)}	V _{DD} =100V, V _{GS} =10V, I _D =11A, R _G =25Ω (Note 1, 2)		11.2		ns
Rise Time	t _R			24		ns
Turn-OFF Delay Time	t _{D(OFF)}			72		ns
Fall-Time	t _F			45		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Body-Diode Continuous Current	I _S				11	A
Maximum Body-Diode Pulsed Current	I _{SM}				33	A
Drain-Source Diode Forward Voltage (Note 1)	V _{SD}	I _S =11A, V _{GS} =0V			1.4	V
Body Diode Reverse Recovery Time (Note 1)	t _{rr}	I _S =11A, V _{GS} =0V, dI _F /dt=100A/μs		430		ns
Body Diode Reverse Recovery Charge	Q _{rr}				3.8	


Notes: 1. Pulse Test : Pulse width ≤ 300μs, Duty cycle ≤ 2%.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit



Peak Diode Recovery dv/dt Waveforms


TEST CIRCUITS AND WAVEFORMS



Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform







Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.