

7N65-TC

Power MOSFET

7.0A, 650V N-CHANNEL
POWER MOSFET

■ DESCRIPTION

The UTC 7N65-TC is a N-channel mode power MOSFET using UTC's advanced technology to provide customers with planar stripe and DMOS technology. This technology allows a minimum on-state resistance and superior switching performance. It also can withstand high energy pulse in the avalanche and commutation mode.


The UTC 7N65-TC is generally applied in high efficiency switch mode power supplies.

■ FEATURES

* $R_{DS(ON)} \leq 1.4 \Omega$ @ $V_{GS}=10V$, $I_D=3.5A$

* High Switching Speed


■ SYMBOL




■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
7N65L-TA3-T	7N65G-TA3-T	TO-220	G	D	S	Tube
7N65L-TF1-T	7N65G-TF1-T	TO-220F1	G	D	S	Tube
7N65L-TF3-T	7N65G-TF3-T	TO-220F	G	D	S	Tube
7N65L-TF3T-T	7N65G-TF3T-T	TO-220F3	G	D	S	Tube
7N65L-TM3-T	7N65G-TM3-T	TO-251	G	D	S	Tube
7N65L-TN3-R	7N65G-TN3-R	TO-252	G	D	S	Tape Reel
7N65L-T2Q-T	7N65G-T2Q-T	TO-262	G	D	S	Tube
7N65L-TQ2-T	7N65G-TQ2-T	TO-263	G	D	S	Tube
7N65L-TQ2-R	7N65G-TQ2-R	TO-263	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

7N65G-TA3-T 	(1)Packing Type (2)Package Type (3)Green Package	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF1: TO-220F1, TF3: TO-220F, TF3T: TO-220F3, TM3: TO-251, TN3: TO-252, T2Q: TO-262, TQ2: TO-263 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--	--

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_c = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	650	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	7	A
	Pulsed (Note 2)	I_{DM}	14	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	700	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	3.3	V/ns
Power Dissipation	TO-220/TO-262	P_D	125	W
	TO-263			
	TO-220F/TO-220F1		35	W
	TO-220F3		55	W
Junction Temperature	TO-251/TO-252			
			+150	°C
Storage Temperature		T_{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=100\text{mH}$, $V_{DD}=50\text{V}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$

4. $I_{SD} \leq 7.0\text{A}$, $dI/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

■ THERMAL DATA

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F	θ_{JA}	62.5	°C/W
	TO-220F1/TO-220F3			
	TO-262/TO-263		110	°C/W
	TO-251/TO-252			
Junction to Case	TO-220/TO-262	θ_{JC}	1.0	°C/W
	TO-263			
	TO-220F/TO-220F1		3.57	°C/W
	TO-220F3			
	TO-251/TO-252		2.27	°C/W


■ ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	650			V
Drain-Source Leakage Current	I_{DSS}	$V_{\text{DS}}=650\text{V}, V_{\text{GS}}=0\text{V}$		10		μA
Gate-Source Leakage Current	Forward	$V_{\text{GS}}=30\text{V}, V_{\text{DS}}=0\text{V}$		100	nA	
	Reverse	$V_{\text{GS}}=-30\text{V}, V_{\text{DS}}=0\text{V}$		-100	nA	
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{\text{GS(TH)}}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=250\mu\text{A}$	2.0		4.0	V
Static Drain-Source On-State Resistance	$R_{\text{DS(ON)}}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=3.5\text{A}$		1.4		Ω
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{ISS}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1.0 \text{ MHz}$		990		pF
Output Capacitance	C_{OSS}			96		pF
Reverse Transfer Capacitance	C_{RSS}			4.2		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge (Note 1)	Q_G	$V_{\text{DS}}=520\text{V}, V_{\text{GS}}=10\text{V}, I_{\text{D}}=7.0\text{A}$ $I_G=1\text{mA}$ (Note 1, 2)		23		nC
Gatesource Charge	Q_{GS}			8.4		nC
Gate-Drain Charge	Q_{GD}			4.6		nC
Turn-on Delay Time (Note 1)	$t_{\text{D(ON)}}$	$V_{\text{DS}}=100\text{V}, V_{\text{GS}}=10\text{V}, I_{\text{D}}=7.0\text{A},$ $R_G=25\Omega$ (Note 1, 2)		12		ns
Rise Time	t_R			17.5		ns
Turn-off Delay Time	$t_{\text{D(OFF)}}$			60		ns
Fall-Time	t_F			27		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Continuous Drain-Source Diode Forward Current	I_S				7	A
Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}				14	A
Drain-Source Diode Forward Voltage (Note 1)	V_{SD}	$I_S=7.0\text{A}, V_{\text{GS}}=0\text{V}$			1.4	V
Reverse Recovery Time (Note 1)	t_{rr}	$I_S=7.0\text{A}, V_{\text{GS}}=0\text{V},$ $dI_F/dt=100\text{A}/\mu\text{s}$ (Note1)		424		ns
Reverse Recovery Charge	Q_{rr}			3.2		μC


Notes: 1. Pulse Test : Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit










Unclamped Inductive Switching Waveforms

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.