



2N60-TC2

Power MOSFET

2A, 600V N-CHANNEL POWER MOSFET



DESCRIPTION

The UTC **2N60-TC2** is a high voltage power MOSFET and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and have a high rugged avalanche characteristics. This power MOSFET is usually used at high speed switching applications in power supplies, PWM motor controls, high efficient AC to DC converters and bridge circuits.

FEATURES

- * $R_{DS(ON)} \leq 5.0 \Omega$ @ $V_{GS}=10V, I_D=1.0A$
- * High Switching Speed

SYMBOL




ORDERING INFORMATION

| Ordering Number | | Package | Pin Assignment | | | Packing |
|-----------------|--------------|----------|----------------|---|---|-----------|
| Lead Free | Halogen Free | | 1 | 2 | 3 | |
| 2N60L-TF1-T | 2N60G-TF1-T | TO-220F1 | G | D | S | Tube |
| 2N60L-TM3-T | 2N60G-TM3-T | TO-251 | G | D | S | Tube |
| 2N60L-TMS-T | 2N60G-TMS-T | TO-251S | G | D | S | Tube |
| 2N60L-TN3-R | 2N60G-TN3-R | TO-252 | G | D | S | Tape Reel |

Note: Pin Assignment: G: Gate D: Drain S: Source

| | |
|--------------------|--|
| <p>2N60G-TF1-T</p> | <p>(1) T: Tube, R: Tape Reel (2) TF1: TO-220F1, TM3: TO-251, TMS: TO-251S TN3: TO-252 (3) G: Halogen Free and Lead Free, L: Lead Free</p> |
|--------------------|--|

MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ($T_C = 25^\circ\text{C}$, unless otherwise specified)

| PARAMETER | | SYMBOL | RATINGS | UNIT |
|------------------------------------|------------------------|-----------|------------|------------------|
| Drain-Source Voltage | | V_{DSS} | 600 | V |
| Gate-Source Voltage | | V_{GSS} | ± 30 | V |
| Drain Current | Continuous | I_D | 2 | A |
| | Pulsed (Note 2) | I_{DM} | 4 | A |
| Avalanche Energy | Single Pulsed (Note 3) | E_{AS} | 61 | mJ |
| Peak Diode Recovery dv/dt (Note 4) | | dv/dt | 2.6 | V/ns |
| Power Dissipation | TO-220F1 | P_D | 23 | W |
| | TO-251/TO-251S | | 44 | W |
| | TO-252 | | | |
| Junction Temperature | | T_J | +150 | $^\circ\text{C}$ |
| Storage Temperature | | T_{STG} | -55 ~ +150 | $^\circ\text{C}$ |

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 10\text{mH}$, $I_{AS} = 3.5\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\ \Omega$ Starting $T_J = 25^\circ\text{C}$

4. $I_{SD} \leq 2.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

■ **THERMAL DATA**

| PARAMETER | | SYMBOL | RATING | UNIT |
|---------------------|----------------|---------------|-------------|---------------------------|
| Junction to Ambient | TO-220F1 | θ_{JA} | 62.5 | $^\circ\text{C}/\text{W}$ |
| | TO-251/TO-251S | | 100 | $^\circ\text{C}/\text{W}$ |
| | TO-252 | | | |
| Junction to Case | TO-220F1 | θ_{JC} | 5.5 | $^\circ\text{C}/\text{W}$ |
| | TO-251/TO-251S | | 2.87 (Note) | $^\circ\text{C}/\text{W}$ |
| | TO-252 | | | |

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.


■ **ELECTRICAL CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|--------------|--|-----|-----|------|----------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=250\mu A$ | 600 | | | V |
| Drain-Source Leakage Current | I_{DSS} | $V_{DS}=600V, V_{GS}=0V$ | | | 10 | μA |
| Gate-Source Leakage Current | Forward | I_{GSS} | | | 100 | nA |
| | Reverse | | | | | |
| | | $V_{GS}=-30V, V_{DS}=0V$ | | | -100 | nA |
| ON CHARACTERISTICS | | | | | | |
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{DS}=V_{GS}, I_D=250\mu A$ | 2.0 | | 4.0 | V |
| Static Drain-Source On-State Resistance | $R_{DS(ON)}$ | $V_{GS}=10V, I_D=1.0A$ | | | 5.0 | Ω |
| DYNAMIC CHARACTERISTICS | | | | | | |
| Input Capacitance | C_{ISS} | $V_{GS}=0V, V_{DS}=25V, f=1.0\text{ MHz}$ | | 250 | | pF |
| Output Capacitance | C_{OSS} | | | 34 | | pF |
| Reverse Transfer Capacitance | C_{RSS} | | | 2.3 | | pF |
| SWITCHING CHARACTERISTICS | | | | | | |
| Total Gate Charge (Note 1) | Q_G | $V_{DS}=480V, V_{GS}=10V, I_D=2A$ $I_G=1\text{ mA}$ (Note 1, 2) | | 6.6 | | nC |
| Gate-source Charge | Q_{GS} | | | 2.6 | | nC |
| Gate-Drain Charge | Q_{GD} | | | 1 | | nC |
| Turn-on Delay Time (Note 1) | $t_{D(ON)}$ | $V_{DS}=100V, V_{GS}=10V, I_D=2.0A,$ $R_G=25\Omega$ (Note 1, 2) | | 5 | | ns |
| Rise Time | t_R | | | 17 | | ns |
| Turn-off Delay Time | $t_{D(OFF)}$ | | | 22 | | ns |
| Fall-Time | t_F | | | 23 | | ns |
| SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS | | | | | | |
| Maximum Body-Diode Continuous Current | I_S | | | | 2 | A |
| Maximum Body-Diode Pulsed Current | I_{SM} | | | | 4 | A |
| Drain-Source Diode Forward Voltage (Note 1) | V_{SD} | $V_{GS}=0V, I_S=2.0A$ | | | 1.4 | V |
| Reverse Recovery Time (Note 1) | t_{rr} | $V_{GS}=0V, I_S=2.0A,$ $di_F/dt=100A/\mu s$ (Note1) | | 300 | | ns |
| Reverse Recovery Charge | Q_{rr} | | | 1 | | μC |


Notes: 1. Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.