

# 20N60K-MT

*Power MOSFET*

## 20A, 600V N-CHANNEL POWER MOSFET

### ■ DESCRIPTION


The UTC **20N60K-MT** is an N-channel Power MOSFET using UTC's advanced technology to provide customers a minimum on-state resistance and superior switching performance, etc.

The UTC **20N60K-MT** is generally applied in high efficient AC to DC converters, PWM motor controls and bridge circuits, etc.

### ■ FEATURES

- \*  $R_{DS(ON)} \leq 0.54 \Omega$  @  $V_{GS}=10V$ ,  $I_D=10A$
- \* High Switching Speed
- \* Improved dv/dt capability

### ■ SYMBOL




### ■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
20N60KL-TF1-T	20N60KG-TF1-T	TO-220F1	G	D	S	Tube
20N60KL-TF2-T	20N60KG-TF2-T	TO-220F2	G	D	S	Tube
20N60KL-TF3T-T	20N60KG-TF3T-T	TO-220F3	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

20N60KG-TF1-T	(1)Packing Type (2)Package Type (3)Green Package	(1) T: Tube (2) TF1: TO-220F1, TF2: TO-220F2, TF3T: TO-220F3 (3) G: Halogen Free and Lead Free, L: Lead Free
---------------	--	--

### ■ MARKING



**■ ABSOLUTE MAXIMUM RATINGS** ( $T_c = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		$V_{DSS}$	600	V
Gate-Source Voltage		$V_{GSS}$	$\pm 30$	V
Drain Current	Continuous	$I_D$	20	A
	Pulsed (Note 2)	$I_{DM}$	40	A
Avalanche Energy	Single Pulsed (Note 3)	$E_{AS}$	731	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	1.9	V/ns
Power Dissipation		$P_D$	44	W
Junction Temperature		$T_J$	+150	$^\circ\text{C}$
Storage Temperature		$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.  
     Absolute maximum ratings are stress ratings only and functional device operation is not implied.  
     2. Repetitive Rating: Pulse width limited by maximum junction temperature.  
     3.  $L = 10\text{mH}$ ,  $I_{AS} = 12.1\text{A}$ ,  $V_{DD} = 50\text{V}$ ,  $R_G = 25 \Omega$  Starting  $T_J = 25^\circ\text{C}$   
     4.  $I_{SD} \leq 20\text{A}$ ,  $di/dt \leq 200\text{A}/\mu\text{s}$ ,  $V_{DD} \leq V_{DSS}$ , Starting  $T_J = 25^\circ\text{C}$

**■ THERMAL DATA**

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient		$\theta_{JA}$	62.5	$^\circ\text{C/W}$
Junction to Case		$\theta_{JC}$	2.84	$^\circ\text{C/W}$

**■ ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$ , unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0\text{V}$ , $I_D=250\mu\text{A}$	600			V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=600\text{V}$ , $V_{GS}=0\text{V}$			10	$\mu\text{A}$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=30\text{V}$ , $V_{DS}=0\text{V}$			100	nA
		$V_{GS}=-30\text{V}$ , $V_{DS}=0\text{V}$			-100	nA
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}$ , $I_D=250\mu\text{A}$	2.0		4.0	V
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=10\text{V}$ , $I_D=10\text{A}$		0.44	0.54	$\Omega$
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	$C_{iss}$	$V_{GS}=0\text{V}$ , $V_{DS}=25\text{V}$ , $f=1.0\text{MHz}$		2450		pF
Output Capacitance	$C_{oss}$			246		pF
Reverse Transfer Capacitance	$C_{rss}$			13		pF
<b>SWITCHING CHARACTERISTICS</b>						
Total Gate Charge (Note 1)	$Q_G$	$V_{DS}=100\text{V}$ , $V_{GS}=10\text{V}$ , $I_D=20\text{A}$ $I_G=1\text{mA}$ (Note 1, 2)		45		nC
Gate-Source Charge	$Q_{GS}$			11		nC
Gate-Drain Charge	$Q_{GD}$			11		nC
Turn-on Delay Time (Note 1)	$t_{D(ON)}$	$V_{DS}=100\text{V}$ , $V_{GS}=10\text{V}$ , $I_D=20\text{A}$ , $R_G=25\Omega$ (Note 1, 2)		26		ns
Rise Time	$t_R$			24		ns
Turn-off Delay Time	$t_{D(OFF)}$			158		ns
Fall-Time	$t_F$			54		ns
<b>SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS</b>						
Maximum Body-Diode Continuous Current	$I_S$				20	A
Maximum Body-Diode Pulsed Current	$I_{SM}$				40	A
Drain-Source Diode Forward Voltage (Note 1)	$V_{SD}$	$V_{GS}=0\text{V}$ , $I_S=20\text{A}$			1.4	V
Reverse Recovery Time (Note 1)	$t_{rr}$	$V_{GS}=0\text{V}$ , $I_S=20\text{A}$ , $dl_F/dt=100\text{A}/\mu\text{s}$ (Note 1)		484		ns
Reverse Recovery Charge	$Q_{rr}$			8.5		$\mu\text{C}$

Notes: 1. Pulse Test : Pulse width  $\leq 300\mu\text{s}$ , Duty cycle  $\leq 2\%$ .


2. Essentially independent of operating temperature.



## ■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery  $dv/dt$  Test Circuit




Peak Diode Recovery  $dv/dt$  Waveforms


### ■ TEST CIRCUITS AND WAVEFORMS




**Switching Test Circuit**




**Switching Waveforms**




**Gate Charge Test Circuit**



**Gate Charge Waveform**









**Unclamped Inductive Switching Test Circuit**










**Unclamped Inductive Switching Waveforms**

## ■ TYPICAL CHARACTERISTICS



## ■ TYPICAL CHARACTERISTICS (Cont.)



**■ TYPICAL CHARACTERISTICS (Cont.)**

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.