




ULTRA LOW CLAMPING BI-DIRECTIONAL ESD TRANSIENT PROTECTION DIODE



DESCRIPTION


The UTC **UESD5V0X1C30** is ultra-low clamping ESD transient bidirectional protection diode, it uses UTC's advanced technology to provide customers with low leakage current and high integration, etc.

The UTC **UESD5V0X1C30** is suitable for ESD protection and high density boards.

FEATURES

- * 350 Watts peak pulse power (8/20μs)
- * Unidirectional Configuration
- * Solid state silicon-avalanche technology
- * Low clamping voltage
- * Low leakage current

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
UESD5V0X1C30L-CB2-R	UESD5V0X1C30G-CB2-R	SOD-323	K	K	Tape Reel

Note: Pin Assignment: K: Cathode A: Anode

<p>UESD5V0X1C30G-CB2-R</p> <p>(1) Packing Type (2) Package Type (3) Green Package</p>	<p>(1) R: Tape Reel (2) CB2: SOT-323 (3) G: Halogen Free and Lead Free, L: Lead Free</p>
---	--

MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT	
ESD Discharge	IEC61000-4-2	Air Discharge	± 30	kV	
		Contact Discharge	± 15	kV	
Peak Pulse Current	IEC61000-4-5	$t_p=8/20 \mu\text{s}$	I_{PP}	20	A
Peak Pulse Power			P_{PK}	350	W
Operating Junction Temperature		T_J	-55 ~ +150	$^\circ\text{C}$	
Operating Temperature		T_{OPR}	-55 ~ +125	$^\circ\text{C}$	
Storage Temperature		T_{STG}	-55 ~ +150	$^\circ\text{C}$	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Stand-Off Voltage	V_{RWM}				5.0	V
Reverse Breakdown Voltage	V_{BR}	$I_R=1\text{mA}$	6.0			V
Reverse Current	I_R	$V_R=5.0\text{V}$			1.0	μA
Clamping Voltage (positive transient)	V_{CL}	$I_{PP}=20\text{A}$, $t_p=8/20\mu\text{s}$, Any Channel pin to Ground			21	V
Diode capacitance	C_d	$V_R=0\text{V}$, $f=1\text{MHz}$			30	pF

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.