



ULN62064

LINEAR INTEGRATED CIRCUIT

PRECISION MICROPOWER SHUNT VOLTAGE REFERENCE


DESCRIPTION

The UTC **ULN62064** is high-voltage, high-current darlington drivers comprised of four NPN darlington pairs.

All units feature integral clamp diodes for switching inductive loads.

For proper operation, the substrate (SUB) must be connected to the most negative voltage.

Applications include relay, hammer, lamp and stepping motor drivers.



DIP-16

FEATURES


- * Output current (single output): 1.5A (Max.)
- * High sustaining voltage output: 50V (Min.)
- * Output clamp diodes
- * Input compatible with TTL and 5V CMOS

ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
ULN62064L-D16-T	ULN62064G-D16-T	DIP-16	Tube

<p>ULN62064G-D16-T</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) T: Tube</p> <p>(2) D16: DIP-16</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
---	--

MARKING




■ PIN CONFIGURATION



■ PIN DESCRIPTION

PIN NO.	PIN NAME	DESCRIPTION
1	COM	Common pin
2	O1	Output pin 1
3	I1	Input pin 1
4	GND	GND pin
5	GND	GND pin
6	I2	Input pin 2
7	O2	Output pin 2
8	COM	Common pin
9	O3	Output pin 3
10	NC	Non-connection pin
11	I3	Input pin 3
12	GND	GND pin
13	GND	GND pin
14	I4	Input pin 4
15	NC	Non-connection pin
16	O4	Output pin 4

■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATING (T_A=25°C, unless other specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Output Sustaining Voltage	V _{CE(SUS)}	-0.5 ~ 50	V
Output Current	I _{OUT}	1.5	A/ch
Input Current	I _{IN}	50	mA
Input Voltage	V _{IN}	-0.5 ~ 17	V
Clamp Diode Reverse Voltage	V _R	50	V
Clamp Diode Forward Current	I _F	1.5	A
Power Dissipation	P _D	1.47/2.7 (Note 2)	W
Operating Temperature	T _{OPR}	-40 ~ +85	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. On Glass Epoxy PCB (50 × 50 × 1.6 mm Cu 50%).

■ OPERATING RANGES (T_A= -40 ~ +85°C, unless other specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Sustaining Voltage	V _{CE(SUS)}		0		50	V
Output Current (Note)	I _{OUT}	DC1 Circuit, T _A =25°C	0		1250	mA/ch
		t _{PW} = 25ms 4 Circuits T _A = 85°C T _J = 120°C	0		1250	mA/ch
		Duty = 10%	0		390	mA/ch
		Duty = 50%	0			
Input Voltage	V _{IN}		0		8	V
Input Voltage (Output On)	V _{IN(ON)}	I _{OUT} = 1.25A	2.5		8	V
Input Voltage (Output Off)	V _{IN(OFF)}		0		0.4	V
Input Current	I _{IN}		0		20	mA
Clamp Diode Reverse Voltage	V _R		0		50	V
Clamp Diode Forward Current	I _F				1.25	A
Power Dissipation	P _D	T _A = 85°C (Note 1)			1.4	W

Note: On Glass Epoxy PCB (50 × 50 × 1.6 mm Cu 50%).

■ ELECTRICAL CHARACTERISTICS (T_A=25°C, unless other specified)


PARAMETER	SYMBOL	TEST CIRCUIT	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Leakage Current	I _{CEX}	1	V _{CE} =50V, T _A =25°C			50	μA
			V _{CE} =50V, T _A =85°C			500	μA
Collector-Emitter Saturation Voltage	V _{CE(sat)}	2	I _{OUT} =1.25A, I _{IN} =2mA			1.6	V
			I _{OUT} =0.75A, I _{IN} =935μA			1.25	V
DC Current Transfer Ratio	h _{FE}	2	V _{CE} =2V	I _{OUT} =1.0A		2500	
				I _{OUT} =1.25A		3000	
Input Voltage (Output On)	V _{IN(ON)}	3	I _{OUT} =1.25A, I _{IN} =2mA			2.4	V
Clamp Diode Leakage Current	I _R	4	V _R =50V, T _A =25°C			50	μA
			V _R =50V, T _A =85°C			100	μA
Clamp Diode Forward Voltage	V _F	5	I _F =1.25A			2	V
Input Capacitance	C _{IN}	6			15		pF
Turn-On Delay	t _{ON}	7	C _L =15pF, V _{OUT} =50V, R _L =42Ω		0.1		μs
Turn-Off Delay	t _{OFF}	7	C _L =15pF, V _{OUT} =50V, R _L =42Ω		1.0		μs

■ SCHEMATICS (EACH DRIVER)




■ TEST CIRCUIT


1. I_{CEX}




2. $V_{CE(sat)}, h_{FE}$




3. $V_{IN(ON)}$




4. I_R



5. V_F




6. C_{iN}



■ TEST CIRCUIT

7. t_{ON} , t_{OFF}



- Notes 1: Pulse Width 50µs, Duty Cycle 10%
 Output Impedance 50Ω, $t_r \leq 5\text{ns}$, $t_f \leq 10\text{ns}$
 2: C_L includes probe and jig capacitance.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.