



UPG11N120ND

Insulated Gate Bipolar Transistor

1200V NPT PLANAR IGBT



■ DESCRIPTION

The UTC **UPG11N120ND** is a 1200V NPT Planar Insulated Gate Bipolar Transistor. it uses UTC's advanced technology to offers superior conduction and switching performance, high avalanche ruggedness and easy parallel operation.

■ FEATURES

- * High speed switching
- * High input impedance
- * Low saturation voltage: $V_{CE(SAT)} = 2.4V @ I_c=11A, V_{GE}=15V$

■ SYMBOL




■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UPG11N120NDL-T47-T	UPG11N120NDG-T47-T	TO-247	G	C	E	Tube
UPG11N120NDL-TQ2-T	UPG11N120NDG-TQ2-T	TO-263	G	C	E	Tube
UPG11N120NDL-TQ2-R	UPG11N120NDG-TQ2-R	TO-263	G	C	E	Tape Reel

Note: Pin Assignment: G: Gate C: Collector E: Emitter

<p>UPG11N120NDG-T47-T</p> <p>(1)Packing Type</p> <p>(2)Package Type</p> <p>(3)Green Package</p>	<p>(1) T: Tube, R: Tape Reel</p> <p>(2) T47: TO-247, TQ2: TO-263</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
---	---

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT	
Collector-Emitter Voltage	V_{CES}	1200	V	
Gate-Emitter Voltage	V_{GES}	± 20	V	
Continuous Collector Current	I_C	$T_C=25^\circ\text{C}$	35	A
		$T_C=110^\circ\text{C}$	17	A
Collector Current Pulsed (Note 1)	I_{CM}	80	A	
Power Dissipation	P_D	TO-247	300	W
		TO-263	90	W
Operating Junction Temperature	T_J	-55 ~ +150	$^\circ\text{C}$	
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$	

Notes: 1. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
 Absolute maximum ratings are those values beyond which the device could be permanently damaged.
 2. Pulse width limited by maximum junction temperature.



■ THERMAL DATA

PARAMETER	SYMBOL	RATING	UNIT	
Junction to Case	θ_{JC}	TO-247	0.42	$^\circ\text{C/W}$
		TO-263	1.39	$^\circ\text{C/W}$

■ ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Collector-Emitter Breakdown Voltage	$B_{V_{CES}}$	$I_C=250\mu\text{A}, V_{GE}=0\text{V}$	1200			V
Collector Cut-Off Current	I_{CES}	$V_{CE}=V_{CES}, V_{GE}=0\text{V}$			250	μA
G-E Leakage Current	I_{GES}	$V_{GE}=V_{GES}, V_{CE}=0\text{V}$			± 250	nA
ON CHARACTERISTICS						
Gate to Emitter Threshold Voltage	$V_{GE(TH)}$	$I_C=250\mu\text{A}, V_{CE}=V_{GE}$	4.5		7.5	V
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=11\text{A}, V_{GE}=15\text{V}$		2.1	2.4	V
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{IES}	$V_{CE}=25\text{V}, V_{GE}=0\text{V}, f=1\text{MHz}$		1510		pF
Output Capacitance	C_{OES}			118		pF
Reverse Transfer Capacitance	C_{RES}			14		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge	Q_G	$V_{CE}=600\text{V}, V_{GE}=15\text{V}, I_C=11\text{A}$		78		nC
Gate-Emitter Charge	Q_{GE}			23		nC
Gate-Collector Charge	Q_{GC}			30		nC
Turn-On Delay Time	$t_{D(ON)}$	$V_{CC}=600\text{V}, V_{GE}=15\text{V}, I_C=11\text{A}, R_G=10\Omega, L=500\mu\text{H}$		10		ns
Rise Time	t_r			17		ns
Turn-Off Delay Time	$t_{D(OFF)}$			52		ns
Fall Time	t_f			266		ns
Turn-On Switching Loss	E_{ON}			0.36		mJ
Turn-Off Switching Loss	E_{OFF}			0.74		mJ

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.