



## MMBTA194

Preliminary

PNP SILICON TRANSISTOR


### HIGH VOLTAGE TRANSISTOR

#### FEATURES

- \* Collector-Emitter Voltage:  $V_{CE0} = -500V$
- \* Collector Dissipation:  $P_{C(MAX)} = 300mW$
- \* Low Collector-Emitter Saturation Voltage

#### APPLICATIONS

- \* Telephone Switching
- \* High Voltage Switch




#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
MMBTA194L-AE3-R	MMBTA194G-AE3-R	SOT-23	B	E	C	Tape Reel

Note: Pin Assignment: B: Base E: Emitter C: Collector

MMBTA194G-AE3-R		
(1) Packing Type	(1) R: Tape Reel	
(2) Package Type	(2) AE3: SOT-23	
(3) Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free	

#### MARKING



■ ABSOLUTE MAXIMUM RATING ( $T_A=25^\circ\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	RATING	UNIT
Collector-Base Voltage	$V_{CB0}$	-500	V
Collector-Emitter Voltage	$V_{CEO}$	-500	V
Emitter-Base Voltage	$V_{EBO}$	-6	V
Collector Current	$I_C$	-300	mA
Collector Dissipation ( $T_a=25^\circ\text{C}$ )	$P_C$	350	mW
Junction Temperature	$T_J$	+150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-40 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	$\theta_{JA}$	357	$^\circ\text{C/W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.

■ ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	$BV_{CBO}$	$I_C = -100\mu\text{A}, I_E=0$	-500			V
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	$I_C = -1\text{mA}, I_B=0$	-500			V
Collector-Emitter Breakdown Voltage	$BV_{CES}$	$I_C = -100\mu\text{A}, V_{BE}=0$	-500			V
Emitter-Base Breakdown Voltage	$BV_{EBO}$	$I_E = -100\mu\text{A}, I_C=0$	-6			V
Collector Cut-off Current	$I_{CBO}$	$V_{CB} = -500\text{V}, I_E=0$			-100	nA
Collector Cut-off Current	$I_{CES}$	$V_{CB} = -500\text{V}, V_{BE}=0$			-1	$\mu\text{A}$
Emitter Cut-off Current	$I_{EBO}$	$V_{EB} = -4\text{V}, I_C=0$			100	nA
DC Current Gain (Note)	$h_{FE}$	$V_{CE} = -10\text{V}, I_C = -1\text{mA}$	60			
		$V_{CE} = -10\text{V}, I_C = -10\text{mA}$	70			
		$V_{CE} = -10\text{V}, I_C = -50\text{mA}$	70			
		$V_{CE} = -10\text{V}, I_C = -100\text{mA}$	40			
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = -10\text{mA}, I_B = -1\text{mA}$			-0.2	V
		$I_C = -50\text{mA}, I_B = -5\text{mA}$			-0.5	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C = -10\text{mA}, I_B = -1\text{mA}$			-0.75	V

Note: Pulse test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.